

FLEX 18 - 2017 JR GOLD U12GB Match Play



Oil Pattern Distance	41	Reverse Brush Drop	36	Oil Per Board	40 ul
Forward Oil Total	17.52 mL	Reverse Oil Total	6.16 mL	Volume Oil Total 23.6	
Tank Configuration	N/A	Tank A Conditioner	FIRE	Tank B Conditioner	FIRE
START STOP LOADS SPEED		ROSSED START END FEET T.OIL			
1 2L 2R 5 14 2 5L 5R 1 14	3 A 3 A	185 0.0 7.9 7.9 7400 31 7.9 9.8 1.9 1240			
2 5L 5R 1 14 3 6L 6R 1 18	3 A 3 A	31 7.9 9.8 1.9 1240 29 9.8 12.3 2.5 1160			
4 7L 7R 2 18	3 A	54 12.3 17.4 5.1 2160		; 50 12 10 2	5 5 5
5 8L 8R 1 18	3 A	25 17.4 19.9 2.5 1000			
6 9L 9R 1 18	3 A	23 19.9 22.4 2.5 920			
7 10L 10R 1 18 8 11L 11R 2 18	3 A 3 A	21 22.4 24.9 2.5 840 38 24.9 30.0 5.1 1520			×
9 12L 12R 1 18	3 A	17 30.0 32.5 2.5 680			~
10 13L 13R 1 18	3 A	15 32.5 35.0 2.5 600			
11 2L 2R 0 22	3 A	0 35.0 37.0 2.0 0			
12 2L 2R 0 26	2 A	0 37.0 41.0 4.0 0			
					÷÷++++++++++++++++++++++++++++++++++++
			II		
START STOP LOADS SPEED	UFFER TANK CR	ROSSED START END FEET T.OIL	— I		
1 2L 2R 0 30	3 B	0 41.0 23.0 -18.0 0			
2 10L 10R 1 22	3 B	21 23.0 19.9 -3.1 840			
3 9L 9R 2 18	4 B	46 19.9 14.8 -5.1 1840			
4 8L 8R 2 18	4 B	50 14.8 9.7 -5.1 2000		******	×
5 2L 2R 1 14 6 2L 2R 0 14	4 B 4 B	37 9.7 7.8 -1.9 1480 0 7.8 0.0 -7.8 0			
6 2L 2R 0 14	4 0	0 1.0 0.0 1.0 0			
					***** ≈
					≈
			1		
Cleaner Ratio Main Mix		NA Forward			γ
Cleaner Ratio Back End N	lix	NA Reverse			
Cleaner Ratio Back End D		NA Combined			
Buffer RPM: 4 = 720 3 =	500 2 = 200	1 = 50			
					~~

Item Description	3L-7L:18L-18R Outside Track:Middle	8L-12L:18L-18R Middle Track:Middle	13L-17L:18L-18R Inside Track:Middle	18L-18R:17R-13R Middle: Inside Track	18L-18R:12R-8R Middle:Middle Track	18L-18R:7R-3R Middle:Outside Track
Track Zone Ratio	2.97	1.25	1	1	1.25	2.97
1500 1330 1200 900 900 750 600 150 0 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2						