## FLEX2N - 2024 PWBA Bowlers Journal Rockford Oper



Oil Pattern Distance **Forward Oil Total Tank Configuration** 

44 16.1 mL Multi Tank

**Reverse Brush Drop Reverse Oil Total Tank A Conditioner** 

38 11.5 mL **Current**  Oil Per Board **Volume Oil Total Tank B Conditioner** 

50 ul 27.6 mL **Fire** 

6 13L 13R 1 18 3 A 15 20.2 22.7 2.5 750 7 15L 15R 2 18 3 A 22 22.7 27.8 5.1 1100 8 2L 2R 0 18 3 A 0 27.8 36.0 8.2 0 9 2L 2R 0 22 3 A 0 36.0 40.0 4.0 0		START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3   7L   7R   1   18   3   A   27   12.7   15.2   2.5   1350     4   9L   9R   1   18   3   A   23   15.2   17.7   2.5   1150     5   11L   11R   1   18   3   A   19   17.7   20.2   2.5   950     6   13L   13R   1   18   3   A   15   20.2   22.7   2.5   750     7   15L   15R   2   18   3   A   22   22.7   27.8   5.1   1100     8   2L   2R   0   18   3   A   0   27.8   36.0   8.2   0     9   2L   2R   0   22   3   A   0   36.0   40.0   4.0   0	1	2L	2R	5	18	3	Α	185	0.0	10.2	10.2	9250
4   9L   9R   1   18   3   A   23   15.2   17.7   2.5   1150     5   11L   11R   1   18   3   A   19   17.7   20.2   2.5   950     6   13L   13R   1   18   3   A   15   20.2   22.7   2.5   750     7   15L   15R   2   18   3   A   22   22.7   27.8   5.1   1100     8   2L   2R   0   18   3   A   0   27.8   36.0   8.2   0     9   2L   2R   0   22   3   A   0   36.0   40.0   4.0   0	2	5L	5R	1	18	3	Α	31	10.2	12.7	2.5	1550
5 11L 11R 1 18 3 A 19 17.7 20.2 2.5 950   6 13L 13R 1 18 3 A 15 20.2 22.7 2.5 750   7 15L 15R 2 18 3 A 22 22.7 27.8 5.1 1100   8 2L 2R 0 18 3 A 0 27.8 36.0 8.2 0   9 2L 2R 0 22 3 A 0 36.0 40.0 4.0 0	3	7L	7R	1	18	3	Α	27	12.7	15.2	2.5	1350
6 13L 13R 1 18 3 A 15 20.2 22.7 2.5 750 7 15L 15R 2 18 3 A 22 22.7 27.8 5.1 1100 8 2L 2R 0 18 3 A 0 27.8 36.0 8.2 0 9 2L 2R 0 22 3 A 0 36.0 40.0 4.0 0	4	9L	9R	1	18	3	Α	23	15.2	17.7	2.5	1150
7 15L 15R 2 18 3 A 22 22.7 27.8 5.1 1100 8 2L 2R 0 18 3 A 0 27.8 36.0 8.2 0 9 2L 2R 0 22 3 A 0 36.0 40.0 4.0	5	11L	11R	1	18	3	Α	19	17.7	20.2	2.5	950
8 2L 2R 0 18 3 A 0 27.8 36.0 8.2 0 9 2L 2R 0 22 3 A 0 36.0 40.0 4.0	6	13L	13R	1	18	3	Α	15	20.2	22.7	2.5	750
9 2L 2R 0 22 3 A 0 36.0 40.0 4.0	7	15L	15R	2	18	3	Α	22	22.7	27.8	5.1	1100
	8	2L	2R	0	18	3	Α	0	27.8	36.0	8.2	0
10 2L 2R 0 26 3 A 0 40.0 44.0 4.0	9	2L	2R	0	22	3	Α	0	36.0	40.0	4.0	0
	10	2L	2R	0	26	3	Α	0	40.0	44.0	4.0	0

2 14L 14R 1 22 3 B 13 36.0 32.9 -3.1 650 3 12L 12R 2 22 3 B 34 32.9 26.7 -6.2 1700 4 10L 10R 2 22 3 B 42 26.7 20.5 -6.2 2100 5 8L 8R 2 18 3 B 50 20.5 15.4 -5.1 2500 6 6L 6R 2 18 3 B 58 15.4 10.3 -5.1 2900 7 4L 4R 1 18 3 B 33 10.3 7.8 -2.5 1650	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 12L 12R 2 22 3 B 34 32.9 26.7 -6.2 1700 4 10L 10R 2 22 3 B 42 26.7 20.5 -6.2 2100 5 8L 8R 2 18 3 B 50 20.5 15.4 -5.1 2500 6 6L 6R 2 18 3 B 58 15.4 10.3 -5.1 2900 7 4L 4R 1 18 3 B 33 10.3 7.8 -2.5 1650	1 2L	2R	0	30	3	В	0	44.0	36.0	-8.0	0
4 10L 10R 2 22 3 B 42 26.7 20.5 -6.2 2100 5 8L 8R 2 18 3 B 50 20.5 15.4 -5.1 2500 6 6L 6R 2 18 3 B 58 15.4 10.3 -5.1 2900 7 4L 4R 1 18 3 B 33 10.3 7.8 -2.5 1650	2 14L	14R	1	22	3	В	13	36.0	32.9	-3.1	650
5 8L 8R 2 18 3 B 50 20.5 15.4 -5.1 2500   6 6L 6R 2 18 3 B 58 15.4 10.3 -5.1 2900   7 4L 4R 1 18 3 B 33 10.3 7.8 -2.5 1650	3 12L	12R	2	22	3	В	34	32.9	26.7	-6.2	1700
6 6L 6R 2 18 3 B 58 15.4 10.3 -5.1 2900 7 4L 4R 1 18 3 B 33 10.3 7.8 -2.5 1650	4 10L	10R	2	22	3	В	42	26.7	20.5	-6.2	2100
7 4L 4R 1 18 3 B 33 10.3 7.8 -2.5 1650	5 8L	8R	2	18	3	В	50	20.5	15.4	-5.1	2500
	6 <b>6L</b>	6R	2	18	3	В	58	15.4	10.3	-5.1	2900
8 2L 2R 0 14 3 B 0 7.8 0.0 -7.8 0	7 4L	4R	1	18	3	В	33	10.3	7.8	-2.5	1650
	8 2L	2R	0	14	3	В	0	7.8	0.0	-7.8	0

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Datio	2.07	1.40	1.05	1.05	1.40	207



